



Summary of EN 12975 Test Results, annex to Solar KEYMARK Certificate	Certificate No.	011-7S1106 R
	Date of issue	26.01.2012

Company	HEWALEX Sp. z o.o. Sp. k.	Country	Poland
Brand (optional)	--	Website	www.hewalex.eu
Street, number	ul. Juliusza Slowackiego, 33	E-mail	hewalex@hewalex.pl
Postal Code	PL-43-502	Tel.	+48 32 214 17 10
City	Czechowice-Dziedzice	Fax	+48 32 214 50 04

Collector Type (flat plate / evacuate tubular / un-glazed)	Evacuated tubular collector
--	-----------------------------

Integration <u>in</u> the roof possible ?	No
---	----

Collector name	Aperture area (Aa) [m <sup>2</sup> ]	Gross length [mm]	Gross width [mm]	Gross height [mm]	Gross area (Ag) [m <sup>2</sup> ]	Power output per collector unit G = 1000 W/m <sup>2</sup> Tm-Ta :				
						0 K	10 K	30 K	50 K	70 K
						[W]	[W]	[W]	[W]	[W]
KSR10	1.014	2'130	856	116	1.823	791	778	751	723	695

Collector efficiency parameters related to <u>aperture area (Aa)</u> Type of fluid and flow rate see note 1	η <sub>0a</sub>	0.780	-
	a <sub>1a</sub>	1.27	W/(m <sup>2</sup> K)
	a <sub>2a</sub>	0.0012	W/(m <sup>2</sup> K <sup>2</sup> )

Stagnation temperature - Weather conditions see note 2	t <sub>stg</sub>	303	°C
--	------------------	-----	----

Effective thermal capacity	C <sub>eff</sub> = C/A <sub>a</sub>	10.3	kJ/(m <sup>2</sup> K)
----------------------------	-------------------------------------	------	-----------------------

Max. operation pressure - see note 3	p <sub>max</sub>	600	kPa
--------------------------------------	------------------	-----	-----

Incidence angle modifiers K <sub>θ</sub> (θ)	G <sub>DIF</sub> /G <sub>TOT</sub>		θ <sub>T</sub> / θ <sub>L</sub>	50°	10°	20°	30°	40°	60°	70°
	min	max	K <sub>θ</sub> (θ <sub>T</sub> )	1.00	1.00	1.00	1.00	1.01	1.00	0.85
	0.1	0.2	K <sub>θ</sub> (θ <sub>L</sub> )	0.94	1.00	1.00	0.99	0.98	0.87	0.74
G <sub>DIF</sub> /G <sub>TOT</sub> : min&max - while measuring					<i>Optional values</i>					

Testing Laboratory	SPF, CH-8640 Rapperswil
Website	www.solarenergy.ch
Test report id. number	C1030LPEN-A1 / C1030QPEN-A1
Date of test report	24.01.2012 / 24.01.2012
Perf. test method	EN 12975-2 6.1.4 (outdoor)

Comments of testing laboratory :	
----------------------------------	--

Note 1	Fluid	Water-Glycole	Flow rate	0.029 kg/s per m <sup>2</sup>	Dr. Andreas Bohren 
Note 2	Irradiance, G <sub>s</sub> =1000 W/m <sup>2</sup>		Ambient temperature , Ta=30 °C		
Note 3	Given by manufacturer				



**Annual collector output based on EN 12975 Test Results,  
annex to Solar KEYMARK Certificate**

Certificate No.

**011-7S1106 R**

Issued

**26.01.2012**

**Annual collector output kWh**

Collector name	Location and collector temperature (Tm)											
	Athens			Davos			Stockholm			Würzburg		
	25°C	50°C	75°C	25°C	50°C	75°C	25°C	50°C	75°C	25°C	50°C	75°C
KSR10	1'336	1'203	1'077	1'227	1'104	987	827	721	628	889	775	675

Collector mounting: Fixed or tracking

Fixed; slope = latitude - 15° (rounded to nearest 5°)

**Overview of locations**

Location	Latitude °	Gtot kWh/m <sup>2</sup>	Ta °C	Collector orientation or tracking mode
Athens	38	1'765	18.5	South, 25°
Davos	47	1'714	3.2	South, 30°
Stockholm	59	1'166	7.5	South, 45°
Würzburg	50	1'244	9.0	South, 35°

Gtot	Annual total irradiation on collector plane	kWh/m <sup>2</sup>
Ta	Mean annual ambient air temperature	°C
Tm	Constant collector operating temperature (mean of in- and outlet temperatures)	°C

Calculation of the annual collector performance is done by the official Solar Keymark spreadsheet tool. Hour by hour the collector output is calculated according to the efficiency parameters from the Keymark test using constant collector operating temperature (Tm). Detailed description with all equations used is available from the Solar Keymark web site (direct link: <http://www.estif.org/solarkeymark/annexb1.php>)

**DIN CERTCO • Alboinstraße 56 • 12103 Berlin**

Tel: +49 30 7562-1131 • Fax: +49 30 7562-1141 • E-Mail: [info@dincertco.de](mailto:info@dincertco.de) • [www.dincertco.de](http://www.dincertco.de)

Datasheet version:

VERSION 3.5, 2012.01.13

Calculation program version:

3.07, October 2011 (SP)